

CURRENT 8 Ampere
VOLTAGE RANG 50 to 1000 Volts

KBU8005 THRU KBU810

特征/Features	外形尺寸/Outline Dimensions
<ul style="list-style-type: none"> ◆ GPP芯片 Glass passivated chip ◆ 低反向漏电流 Low Reverse Leakage Current ◆ 高耐浪涌电流能力 High surge current capability ◆ 接线端与壳体间绝缘耐压2500V Case to Terminal Isolation Voltage 2500V 	<p>Case: KBU Series Dimensions in millimeters</p>
机械参数/Mechanical Data	<ul style="list-style-type: none"> ◆ 本体: 塑封 Case: plastic package ◆ 标识/极性: 本体标记 Marking / Polarity: Marked on Body ◆ 重量: 约克 Weight: About 6.66 grams

极限值/Maximum Ratings and Thermal Characteristics @ Ta = 25°C unless otherwise noted

符号 Symbol	特性 Characteristic	KBU8							单位 Unit
		005	01	02	04	06	08	10	
VRRM	最大反向重复峰值电压 Maximum Recurrent Peak Reverse Voltage	50	100	200	400	600	800	1000	V
IF (AV)	平均整流输出电流 Average Forward Output Rectified Current@Ta = 85°C				8				A
VF	正向峰值电压 Forward Voltage Per Leg @IFM = 8.0A				1.1				V
IFSM	正向浪涌电流 Peak Forward Surge Current 8.3ms Single Half Sine-wave superimposed on rated load				160				A
IR	反向漏电流 Maximum DC reverse current at rated DC blocking voltage per leg	Ta = 25°C Ta = 125°C			5				uA
i ² t	热容值 Rating for fusing (t<8.3ms)				106				A ² S
Visol	绝缘耐压 Rms isolation voltage from case to leads				2500				V
R _{θJC}	热阻 Maximum thermal resistance per leg				4.2				°C/W
T _j , T _{STG}	结温, 存储条件 Operating Junction and storage temperature range				-55~150				°C

Note:

- (1) Junction to case with heatsink
- (2) Recommended mounting position is to bolt down on heatsink with silicone thermal compound for maximum heat transfer with M3 screw .

CURRENT 8 Ampere
VOLTAGE RANG 50 to 1000 Volts

KBU8005 THRU KBU810

■特性曲线（典型） Characteristics(Typical)

