

CURRENT 1.0 Ampere  
 VOLTAGE RANG 50 to 1000 Volts


# HER101 THRU HER108

## FEATURES

- Low coat construction
- Fast switching for high efficiency.
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed:  
 260 /10 secods/.375 (9.5mm)lead length at 5 lbs(2.3kg) tension

## MECHANICAL DATA

- Case: Transfer molded plastic
- Epoxy: UL94V-O rate flame retardant
- Polarity: Color band denotes cathode end
- Lead: Plated axial lead, solderable per MIL-STD-202E method 208C
- Mounting position: Any
- Weight: 0.012ounce, 0.33 grams



Dimensions in inches and (millimeters)

## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	HER 101	HER 102	HER 103	HER 104	HER 105	HER 106	HER 107	HER 108	UNITS
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	50	100	200	300	400	600	800	1000	Volts
Maximum RMS Voltage	$V_{RMS}$	35	70	140	210	280	420	560	800	Volts
Maximum DC Blocking Voltage	$V_{DC}$	50	100	200	300	400	600	800	1000	Volts
Maximum Average Forward Rectified Current 0.375 (9.5mm) lead length at $T_A=50$	$I_{(AV)}$	1.0								Amp
Peak Forward Surge Current 8.3mS single half sine wave superimposed on rated load (JEDEC method)	$I_{FSM}$	30								Amps
Maximum Instantaneous Forward Voltage @ 1.0A	$V_F$	1.0		1.3		1.5		1.7		Volts
Maximum DC Reverse Current at Rated DC Blocking Voltage	$T_A=25$	5.0								$\mu A$
	$T_A=125$	250								
Maximum Full Load Recovery Current,full cycle average 0.375 (9.5mm)lead length at $T_L=55$	$I_{R(AV)}$	100								$\mu A$
Maximum Reverse Recovery Time (NOTE1)	$t_{rr}$	50				75				ns
Typical Thermal Resistance (NOTE 2)	$C_J$	15				12				PF
Typical Thermal Resistance(NOTE 3)	$R_{\theta JA}$	60								/W
Operating Junction Temperature Range	$T_J T_{STG}$	(-55 to +150)								

### Notes:

1. Test Conditions:  $I_f=0.5mA, I_r=1.0mA, I_{rr}=0.25A$
2. Measured at 1 MHz and applied reverse of 4.0 volts.
3. Thermal resistance from junction to ambient with .375 (9.5mm)lead length, P.C.B. mounted.

CURRENT 1.0 Ampere  
 VOLTAGE RANG 50 to 1000 Volts

**HER101 THRU HER108**

RATING AND CHARACTERISTIC CURVES HER101 Thru HER108

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE




FIG.4-TYPICAL REVERSE CHARACTERISTICS





FIG.6-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC



NOTE: 1. Rise Time = 7ns max. Input Impedance = 1megohm. 22pF  
 2. Rise time = 10ns max. Source Impedance = 50 ohms

SET TIME BASE FOR 50 / 100NS /cm