

CURRENT 2.0 Ampere  
 VOLTAGE RANG 50 to 1000 Volts

## S2A THRU S2M


### FEATURES

- Plastic package has underwrites laboratory flammability Classification 94V-0
- For surface mounted applications
- Low profile package
- Built-in strain relief, ideal for automated placement
- Glass Passivated chip junction
- High temperature soldering guaranteed
- 250°C/10 second at terminals

### MECHANICAL DATA

Case: JEDED DO-214AC molded plastic over glass passivated chip  
 Terminals: Solder plated, Solderable per MIL-STD-750, method 2026  
 Polarity: Color band denotes cathode end  
 Weight: 0.002ounce, 0.064 gram

### DO-214AC (SMA)



Dimensions in inches and (millimeters)

### MAXIMUM RATINGS & THERMAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified

	SYMBOLS	S2A	S2B	S2D	S2G	S2J	S2K	S2M	UNIT
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage	$V_{RMS}$	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current at $T_L=100^\circ\text{C}$	$I_{F(AV)}$	2.0							Amps
Peak Forward Surge Current 8.3ms single half sine wave superimposed on rated load (JEDEC method) $T_L=100^\circ\text{C}$	$I_{FSM}$	50							Amps
Typical Thermal Resistance (NOTE 1)	$R_{\theta JA}$	53							°C/W
	$R_{\theta JL}$	16							
Operating and Storage Temperature Range	$T_J, T_{STG}$	-55 to +150							°C

### ELECTRICAL CHARACTERISTICS

	SYMBOLS	S2A	S2B	S2D	S2G	S2J	S2K	S2M	UNIT
Maximum Instantaneous Forward Voltage at 1.5A	$V_F$	1.15							Volts
Maximum DC Reverse Current at rated DC Blocking Voltage	$T_A = 25^\circ\text{C}$	5.0							µA
	$T_A = 125^\circ\text{C}$	125							
Typical Reverse Recovery Time at $I_F=0.5A, I_R=1.0A, I_{RR}=0.25A,$	$T_{rr}$	2.0							µs
Typical junction capacitance at 4.0V, 1MHz	$C_J$	30							pF

#### Notes:


- Thermal resistance from Junction to ambient and from junction to lead mounted on P.C.B.with 0.3×0.3" (8.0 × 8.0mm) copper pad areas.

CURRENT 2.0 Ampere  
 VOLTAGE RANG 50 to 1000 Volts


**S2A THRU S2M**

RATING AND CHARACTERISTIC CURVES S2A Thru S2M


F1G.1-FORWARD CURRENT DERATING CURVE




F1G.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT



F1G.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS



F1G.4-TYPICAL REVERSE CHARACTERISTICS



F1G.5-TYPICAL JUNCTION CAPACITANCE

